



BOX2/4 control unit together with the Safety Light Curtains TYPE 2 (model OPT3 SMC PXXX) upgrades the category to TYPE 4.


The control unit has got an input for the connection of the final switches of the light curtain which controls their disparity and supplies in its output the two contacts NC, in state of alert, coming from the two safety relays at guided contacts in redundancy selfcontrolled

Moreover the control unit provides these functions :

- **External Device Monitoring (EDM)** : control of the external devices : for example contactor, relay, etc...
- **Led Diagnostic** for failures signalling and detection
- **Contact AUX (Ausiliary) NC** normally closed

TECHNICAL FEATURES


Power Supply	24Vdc \pm 10%
Absorption	60 mA
Type 2 Inputs	2 NO (switches SW1 - SW2)
Type 4 Outputs	2 NO (switches SW3 - SW4)
Outputs Current	5A @ 250Vac
Outputs Protection	fuses 5A
Contact AUX	1 NC - 3 A max (no safety)
Response Time	6 milliseconds
Housing	Blend PC/ABS self-autoextinguishing DIN RAIL (EN60715)
Housing Section	101 x 119 x 35 mm
Protection Degree	IP20
Working Temperature	0 / +55 °C
Directives	2006/42/CE - 2004/108/CE - 2006/95/CE
Standards	CEI-EN 61496/1 - CEI-CLC/TS 61496-2



N.B. The unit "BOX2/4" is provide with the EDM function temporarily disabled (jumper on terminal EDM).

If it becomes necessary to use other external devices (relays, etc...) to increase the output contacts, it is recommended to control the safety of these devices by remove the jumper in the terminal EDM and connect the contact or contacts NC of such devices in series in the terminal EDM.

MECHANICAL DIMENSIONS (millimeters)



HOW TO ORDER

Product Code

BOX 2/4



Via Pergolesi 30 - 20851 LISSONE (MB) - www.elindco.it

DECEMBER 2012

The manufacturer has the right to modify the products and the details contained in this TECHNICAL SHEET whenever necessary without previous notification.
EL.IND.CO. is not responsible for an improper use of its products.

page 2/2